



PRO PORTABLE CHARGER

Product size:
255x109x55 mm



Parameters

Specification	Model:	TS-PEC-002-16A	TS-PEC-002-32A
Electrical properties	Voltage:	230V AC	230V AC
	Output current:	16A (6/8/10/13/16A optional)	32A (8/10/13/16/20/32A optional)
	Output power:	3.6 kW	7 kW
	Cable specification:	3x2.5 mm ² +2x0.5 mm ²	3x6 mm ² +2x0.5 mm ²
	Frequency:	50/60 Hz	
Structure design	Residual current protection:	30mA AC or 30mA AC + 6mA DC	
	Display:	1.8 inch LCD	
	LED indicator:	LED light bar	
	Front panel:	PMMA	
	Installation method:	Wall-mount, carry on optional	
	Charging outlet:	Type1/Type2 + 4 meter charging cable	
	Housing material:	PC + GF 10%	
Security protection	Safety standard:	IEC / EN 62752:2016	
	Multiple protection:	Over/under voltage protection, surge protection, over temperature protection, over current protection, leakage protection, short circuit protection, EFT protection	
	Warranty:	1 year	
Environmental performance	Working temperature:	-30 °C - +60 °C	
	Storage temperature:	-40 °C - +70 °C	
	Working humidity:	5%-95%, no condensation	
	Protection level:	IP67	
	Application site:	Indoor/outdoor	
	Cooling method:	Natural cooling	
Extra function	Temperature detection function:	Yes (Check the temp. of PCB and show it on the screen)	
	Schedule charging:	Yes (1-8 hours)	
Packing details	Product size:	255x109x55 mm	
	Product weight:	2.7 kg	3.3 kg