



PRO INDUSTRIAL CHARGER

Product size:
398x324x120 mm



Parameters

Specification	Model:	TS-EVC07-002	TS-EVC11-002	TS-EVC22-002
Electrical properties	Voltage:	230V AC	380V AC	380V AC
	Output current:	32A (1 phase)	16A (3 phase)	32A (3 phase)
	Output power:	7 kW	11 kW	22 kW
	Frequency:	50/60 Hz	50/60 Hz	50/60 Hz
Structure design	Emergency stop buton:	Yes		
	Residual current protection:	Type A (30mA AC)		
	Display:	5 inch LCD screen		
	RFID function:	3 pcs RFID card		
	Installation method:	Wall-mount/Floor-stand		
	Charging outlet:	4 meter charging cable with Type1/Type2 plug		
	Front panel:	PC		
Security protection	Housing material:	PCV0 for outdoor		
	Safety standard:	EN 61851-1		
	Warranty:	2 year		
	Protection level:	IP67		
Environmental performance	Application site:	Indoor/outdoor		
	Working temperature:	-30 °C - +50 °C		
Communication	Working humidity:	5%-95%, no condensation		
	Communication protocol:	Modbus RS485		
Packing details	Product size:	398x324x120 mm		
	Product weight:	7 kg	8.2 kg	8.5 kg
Optional	Residual current protection:	Type B (30mA AC + 6mA DC)		
	Energy meter:	MID certified		